



GOLDEN STATE INSTRUMENT CO.

GS-PTZ-2311X

GS-PTZ-1811X

Intelligent High -Speed Dome Camera (Indoor)

Features:

- High die-cast aluminum construction
- Low noise design
- Left and right rotation range: 360° continuous rotation
- Left and right speed: 0°-300°/second
- Up and down rotation range: 0-90°
- Up and down speed: 0°-120°/second
- Communication: RS485
- Controlled rotation range: up and down, left and right
128 preset positions
- Left and right line scanning: variable speed
- 6 Guard Tours / 16 points per tour



Specification

Model	GS-PTZ-2311X	GS-PTZ-1811X
Image sensor	1/4"Sony EXVIEW HAD Color CCD	
Active pixels	758(H)x504(V)	768(H)x494(V)
Synchronization	Internal/External	
Video output	VBS 1.0Vp-p/75 ohms	
White balance	Auto / Manual	
Backlight compensation	On/off	
Horizontal resolution	480TVL	
S/N ratio	≥50dB	
Electronic shutter	1/3~1/10000s	
Min.illumination	Typical:1Lux/F1.2 Star light mode:0.01Lux/F1.2	
Focal length	f =3.6~82.8mm	f =4.1~73.8mm
Magnification	23x optical, 10x digital	18x optical, 10x digital
Focal & iris	Auto	
Input voltage	AC24V	
Power consumption	about 15W	
Work temperature	0°C - 40°C	
Preset	128	
Communication	Multi-protocol, RS485	
Dimension	φ5.4"(137mm)xH8"(205mm)	
Weight	2Kg	

14256 Doolittle Drive · San Leandro, CA 94577 · 1-800-227-2330 · Fax(510)352-5988

Website: www.goldenstateinst.com · E-mail: gsi@goldenstateinst.com