



GOLDEN STATE INSTRUMENT CO.



GS-NVR4CH

1.3 Megapixel 4 Channel Network Video Recorder



The GS-NVR4CH is the most simple NVR (Network Video Recorder) to configure and setup. Its Turn-Key NVR features GSI Auto-Connect which connects all cameras with one click of a button. With a built in 4 Port Switch, you can connect all 4 GSI HDIP cameras directly to the back of the NVR. It is compatible with all GSI 1.3 Megapixel IP cameras. These cameras produce a stunning picture quality with a resolution of 1280 x 1024. HDIP cameras deliver realistic lifelike colors unmatched by traditional analog cameras.



Features:

- GSI Auto-Connect: Connect all cameras with one click
- H.264 Compression: Lowers Hard Drive Consumption and reduce bandwidth requirements
- VGA and HDMI outputs for HD Monitor Display
- Built in Switch for Plug and Play
- Supports all GSI's 1.3MP HDIP Cameras
- Remote Viewing over the network with Internet Explorer or with Secuguard Software(Live Only)
- SD Card Backup (SD Card not Included)
- Easy to use GUI
- 1280x1024 Recording Resolution
- 4 Channel Simultaneous Playback
- USB Mouse Included
- 2 Way Audio
- Snapshot Function
- Hard Drive Configurations Up to 2TB

Typical Configuration

Built in 4 Port Switch



Quad View



HDIP Cameras

HDMI or VGA Monitor



3002 Dow Ave Suite 228
Tustin, CA 92780 USA

www.goldenstateinst.com

Sales : 800-227-2330
Tech Support: 888-808-0909
Email : gsi@goldenstateinst.com

| | |
|-----------------------|---|
| MODEL | GS-NVR4CH |
| Channels | 4 |
| RAM | 256MB (2 x 128MB) |
| ROM | NAND Flash ROM 128MB |
| LAN Ports | 5 x 10/100M RJ-45 Ethernet Ports |
| Video Outputs | 1 x VGA D-Sub and 1 x HDMI |
| Display Resolution | 1024 x 768 |
| Recording Resolution | QQVGA, QVGA, VGA, SXGA |
| IP Camera Supported | GS-825 MIPC GS-830 MIPC GS-832 MIPC GS-835 MIPC GS-840 MIPC GS-870 MIPC GS-880 MIPC |
| Compression | H.264 |
| Frames Per Second | 15FPS Max Per Channel |
| Hard Drive Capacity | 500GB, 1TB, 2TB |
| Protocol | TCP, UDP, HTTP |
| Rate Control | CBR (Constant Bit Rate) VBR (Variable Bit Rate) |
| Playback | 4 Channel Simultaneous playback |
| Audio | 3.5mm 1 x input and 1 x output |
| HDD | 1 x SATAII 3.5inch (Up to 2TB Supported) |
| Backup | 1 x SD Card (Not Included) |
| LED Indicator | System Ready, HDD, LAN (5 Ports) |
| USB | USB Mouse Controls (Included) |
| Button | Factory Reset and Power Switch |
| Operation | Triplex (Live View, Recording, Setting) |
| Easy Install | GSI Auto Setting |
| Remote View | Internet Explorer, Secuguard Software (Live View) |
| Certification | CE, FCC |
| Video Buffer | Pre and Post alarm buffering |
| Motion Detection | Yes |
| Power Supply | External Adaptor, 12 VDC 3A |
| Operating Temperature | 0~40°C |
| Humidity | 0%~85% R.H. |
| Dimensions | W 12.6" x D 8.3" x H 2" |
| Weight | 3.4 lbs (Hard Drive not Included) |